

ZP54K5E-PFV

HFC, R-410A, 60 Hz, 1 - Phase, 208/230 V

**Air Conditioning**

**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance			Mechanical	
Evaporator Temp. (°F)	45.00	50	Displacement (in <sup>3</sup> /Rev):	3.12
Condensing Temp. (°F)	130.00	100	Displacement (ft <sup>3</sup> /Hr):	
Return Gas Temp. (°F)	65.00	70	Overall Length (in):	9.69
Liquid Temp. (°F)	115.00	85	Overall Width (in):	9.69
Capacity (BTU/hr)	54000	74000	Overall Height (in):	16.46
Power (W):	5150	3460	Mounting Length (in):	7.50
Current (Amps):	22.5	15.4	Mounting Width (in):	7.50
EER(BTU/Wh):	10.5	21.4	Mounting Height (in):	17.21
Mass Flow (lbs/hr):	800	910	Suction Size (in),Type:	7 / 8 Stub
Sound Data @ 45 / 130			Discharge Size (in),Type:	1 / 2 Stub
Sound Power (dBA):	68 Avg	73 Max	Initial Oil Charge (oz):	42
Vibration mils(peak-peak):	2.0 Avg	3.0 Max	Oil Recharge (oz):	36
Record Date:	2017-03-01		Oil Type:	3MA
			Net Weight (lbs):	75.7
			Internal Free Volume (in <sup>3</sup> ):	176.9
			Horse Power:	
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors				
		Type	Part No	Low MFD	High MFD	Volts User Description
LRA High* (Amps):	134.0	No data available in table				
LRA Low*(Amps):						
LRA Half Winding (Amps):						
MCC (Amps):	41					
Max Operating Current (Amps):	36.00					
RLA, MCC/1.4(use for contactor selection)(Amps):	29.3					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	26.3					
RPM:	3500					
Box IP :	21					
UL File No:	SA-2337					
UL File Date:	2003-12-17					

\*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

## Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
-------------	---------	-------	-----------	-------------