

ZR54K5E-PFV

HFC, R-407C, 60 Hz, 1 - Phase, 208/230 V

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance			Mechanical	
Evaporator Temp. (°F)	45.00	50	Displacement (in ³ /Rev):	4.40
Condensing Temp. (°F)	130.00	100	Displacement (ft ³ /Hr):	
Return Gas Temp. (°F)	65.00	70	Overall Length (in):	9.69
Liquid Temp. (°F)	115.00	85	Overall Width (in):	9.69
Capacity (BTU/hr)	50100	69400	Overall Height (in):	16.43
Power (W):	4850	3250	Mounting Length (in):	7.50
Current (Amps):	21.8	14.8	Mounting Width (in):	7.50
EER(BTU/Wh):	10.3	21.4	Mounting Height (in):	17.18
Mass Flow (lbs/hr):	729	855	Suction Size (in),Type:	7 / 8 Stub
Sound Data @ 45 / 130			Discharge Size (in),Type:	1 / 2 Stub
Sound Power (dBA):	70 Avg	75 Max	Initial Oil Charge (oz):	42
Vibration mils(peak-peak):	2.0 Avg	3.0 Max	Oil Recharge (oz):	34
Record Date:	2015-10-13		Oil Type:	3MA
			Net Weight (lbs):	72.5
			Internal Free Volume (in ³):	179.0
			Horse Power:	4.5
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors					
LRA High* (Amps):	146.0	Type	Part No	Low MFD	High MFD	Volts	User Description
LRA Low*(Amps):		No data available in table					
LRA Half Winding (Amps):							
MCC (Amps):	39.5						
Max Operating Current (Amps):	34.00						
RLA, MCC/1.4(use for contactor selection)(Amps):	28.2						
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	25.3						
RPM:	3500						
Box IP :	21						
UL File No:	SA-2337						
UL File Date:							

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
-------------	---------	-------	-----------	-------------